

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 February 2005 (24.02.2005)


PCT

(10) International Publication Number
WO 2005/016781 A1

- (51) International Patent Classification⁷: **B65D 75/58**
- (21) International Application Number:
PCT/EP2004/009251
- (22) International Filing Date: 17 August 2004 (17.08.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
03018560.7 18 August 2003 (18.08.2003) EP
- (71) Applicant (for all designated States except US): NESTEC
S.A. [CH/CH]; Avenue Nestlé 55, CH-1800 Vevey (CH).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): JEANNIN, Bernard
[FR/FR]; 21, rue Rene Coty, F-80080 Amiens (FR).
- (74) Agents: LOCK, Graham, James et al.; Fry Heath &
Spence LLP, The Gables, Massetts Road, Horley, Surrey
RH6 7DQ (GB).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.
- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: FLEXIBLE PACKAGING AND METHOD OF MANUFACTURE



(57) Abstract: A wall material for a construction of a flexible container that is designed to be openable by tearing is formed by providing a flexible film for forming a wall of the container, providing a tear barrier element having greater tear resistance than the wall film, locating the element on or within the film to define a tear path thereon, and fixing the element to the film. The film is then arranged to form a flexible-walled container having opposed back and front walls, so that the tear path is spaced from at least a part of the top edge thereof and facilitates opening of the container by restricting tearing to the path defined between the strips. The tear barrier strips may be located to be fixed on the film by means of suitable adhesive or may be embedded between laminate layers of the wall material.



FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments*

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*